

Appl. 10/631,881

Attorney Docket 9046/20

Non-final Office Action mailed February 7, 2005

Amendment transmitted April 29, 2005

**In the Claims:**

This listing replaces all previous listings and versions of claims in the application.

1. (Currently amended) A flashing light system, comprising:
  - a controller;
  - a power source connected to the controller;
  - a switch connected to at least one of the power source and the controller;
  - and
  - a plurality of lamps connected to the controller, wherein the switch and the controller activate the plurality of lamps to display an alphanumeric character by quickly flashing the lamps in a sequence, and wherein the controller flashes the lamps in a first sequence when the switch closes at a low frequency, and the controller flashes the lamps in a second sequence when the switch closes at a higher frequency.
2. (Original) The system of Claim 1, wherein the plurality of lamps comprises at least three LEDs arranged in a column.
3. (Currently amended) The system of Claim 1, wherein the switch comprises a motion switch ~~and the controller flashes the lamps in a first sequence when the motion switch closes at a low frequency, and the controller flashes the lamps in a second sequence when the motion switch closes at a higher frequency.~~
4. (Original) The system of Claim 3, wherein the low frequency is less than 3 Hz.

Appl. 10/631,881  
Non-final Office Action mailed February 7, 2005  
Amendment transmitted April 29, 2005

Attorney Docket 9046/20

5. (Original) The system of Claim 3, wherein the plurality of lamps comprises a first display and a second display of at least three LEDs each, and the controller flashes the lamps of the first display with a predetermined pattern when the motion switch is closed at a low frequency, and the controller flashes the lamps of the second display with a pattern when the motion switch is closed at a greater frequency.

6. (Original) The system of Claim 5, wherein the controller is a CMOS controller.

7. (Original) The system of Claim 1, further comprising a memory of the controller or a memory accessible to the controller, the memory storing data defining at least two patterns at least two patterns of alphanumeric characters, wherein the sequence displayed is responsive to a frequency of the switch closing.

8. (Original) The system of Claim 7, wherein the patterns of alphanumeric characters comprise a sequential pattern, a forward pattern, a reversed pattern, a random pattern, a fade-in sequential pattern and a fade-out sequential pattern.

9. (Original) The system of Claim 7, wherein the controller comprises at least two NAND circuits.

10. (Original) The system of Claim 1, wherein the lamps comprise LEDs in a display, and the LEDs in the display are separated vertically by not more than 2 mm.

Appl. 10/631,881  
Non-final Office Action mailed February 7, 2005  
Amendment transmitted April 29, 2005

Attorney Docket 9046/20

11. (Original) The flashing light system of Claim 1, further comprising footwear into which the system is assembled.

12. (Original) The system of Claim 1, wherein the power source comprises two batteries and wherein at least one of the plurality of LEDs is connected to two different voltages in the sequence.

13. (Original) The system of Claim 1, further comprising a second plurality of lamps connected to the power source and the controller.

14. (Original) The system of Claim 13, further comprising a memory accessible to the controller, the memory storing data defining at least two patterns for flashing the lamps.

15. (Original) The system of Claim 13, further comprising a plastic display, wherein the second plurality of lamps is embedded in the plastic display.

16. (Original) The system of Claim 13, wherein the power source comprises two batteries and wherein at least one of the LEDs in the first plurality and the second plurality is connected to two different voltages in sequence.

17. (Original) The system of Claim 1, further comprising a battery charger.

18. (Original) The system of Claim 1, further comprising a personal accessory.

Appl. 10/631,881  
Non-final Office Action mailed February 7, 2005  
Amendment transmitted April 29, 2005

Attorney Docket 9046/20

19. (Original) A method of displaying a message, the method comprising:  
wearing an item selected from the group consisting of footwear, an article  
of clothing, and a personal accessory, the item further comprising the flashing  
light system of Claim 1;  
activating the flashing light system; and  
displaying the message.

20. (Currently amended) A method of displaying a message, the method  
comprising:

furnishing a flashing light system in footwear, an article of clothing, or a  
personal accessory, the flashing light system further comprising a controller, a  
power source connected to the controller, a switch connected to at least one of  
the power source and the controller, and a plurality of lamps connected to the  
controller;

activating the flashing light system; and  
displaying a message by quickly flashing the lamps in sequence, wherein  
the lamps flash at least two alphanumeric characters in a sequence to form the  
message, and wherein a first message is displayed when the switch is closed at  
a low frequency, and a second message is displayed when the switch is closed  
at a higher frequency.

21. (Original) The method of Claim 20, wherein moving the switch is  
accomplished by one of touching the switch, toggling the switch, and moving the  
footwear or personal accessory to close an inertia switch.

Appl. 10/631,881  
Non-final Office Action mailed February 7, 2005  
Amendment transmitted April 29, 2005

Attorney Docket 9046/20

22. (Currently amended) The method of Claim 20, wherein the switch is an inertia switch, and a first message is displayed when the inertia switch is closed at a low frequency, and a second message is displayed when the inertia switch is closed at a higher frequency.

23. (Original) The method of Claim 20, wherein the flashing light system further comprises a second plurality of lamps, and wherein the method further comprises flashing at least one pattern with the second plurality of lamps.

24. (Currently amended) A flashing light system, comprising:  
a controller;  
a power source connected to the controller;  
a switch connected to at least one of the power source and the controller;  
a first plurality of LEDs connected to the controller, wherein the switch and the controller activate the first plurality of LEDs to display an alphanumeric character by flashing the LEDs in a sequence; and  
a second plurality of LEDs connected to the controller, wherein the switch and the controller activate the second plurality of LEDs to display at least one pattern, and wherein the power source comprises two batteries and wherein at least one of the first and second plurality of LEDs is connected to two different voltages in sequence.

25. (Original) The system of Claim 24, wherein the switch is selected from the group consisting of an inertia switch, a touch switch, and a toggle switch.

26. (Canceled)

Appl. 10/631,881  
Non-final Office Action mailed February 7, 2005  
Amendment transmitted April 29, 2005

Attorney Docket 9046/20

27. (Original) The system of Claim 24, further comprising a plastic display, wherein the second plurality of LEDs is embedded within the plastic display.

28. (Original) The flashing light system of Claim 24, further comprising footwear containing the system.

29. (Original) The flashing light system of Claim 24, further comprising a personal accessory containing the system.

30. (Original) A flashing light system, comprising:  
a controller;  
a power source connected to the controller;  
an inertia switch connected to at least one of the power source and the controller; and

a first and a second plurality of lamps connected to the controller, wherein when the inertia switch closes at a low frequency the controller activates the first plurality of lamps, and when the inertia switch closes at a high frequency, the controller activates the second plurality of lamps.

31. (Original) The flashing light system of Claim 30, wherein, at the low frequency, the controller activates the first plurality of lamps to display at least one alphanumeric character by quickly flashing the lamps in a sequence.

32. (Original) The flashing light system of Claim 30, wherein, at the higher frequency, the controller activates the second plurality of lamps to display at least one alphanumeric character by quickly flashing the lamps in a sequence.

Appl. 10/631,881  
Non-final Office Action mailed February 7, 2005  
Amendment transmitted April 29, 2005

Attorney Docket 9046/20

33. (Original) The flashing light system of Claim 30, wherein the low frequency is less than 3 Hz.

34. (Original) The flashing light system of Claim 30, wherein the first plurality and the second plurality each comprise at least three LEDs.

35. (Original) The system of Claim 30, further comprising a plastic display, wherein the second plurality of LEDs is embedded within the plastic display.

36. (Original) The flashing light system of Claim 30, further comprising footwear containing the flashing light system.

37. (Original) The flashing light system of Claim 30, further comprising a personal accessory containing the flashing light system.

38. (Original) A flashing light system, comprising:  
a controller;  
a power source connected to the controller;  
an inertia switch connected to at least one of the power source and the controller; and

a plurality of lamps connected to the controller, wherein when the inertia switch closes at a low frequency the controller activates the plurality of lamps to display a first pattern, and when the inertia switch closes at a higher frequency the controller activates the plurality of lamps to display a second pattern.

Appl. 10/631,881  
Non-final Office Action mailed February 7, 2005  
Amendment transmitted April 29, 2005

Attorney Docket 9046/20

39. (Original) The flashing light system of Claim 38, wherein at least one of the first pattern and the second pattern comprises at least one alphanumeric character.

40. (Original) The flashing light system of Claim 38, wherein the controller comprises at least two NAND circuits.

41. (Original) The flashing light system of Claim 38, wherein the lamps comprise LEDs in a display, and the LEDs are separated horizontally by about 2-3 mm.

42. (Original) The flashing light system of Claim 38, further comprising footwear containing the flashing light system.

43. (Original) The flashing light system of Claim 38, wherein the low frequency is less than 3 Hz.

44. (Original) The flashing light system of Claim 38, wherein at least one of the first pattern and second pattern is a random pattern.